

HM Walk is engineered with a .6mm wear layer and a glueless Valinge click system to provide exceptional value and ease of installation. Five of Australia's most renowned timbers shine in today's flooring trend of wider widths and long lengths. With a durable wear surface of strong Australian hardwood and an extremely stable 9 ply plantation Eucalypt core, HM Walk can be floated or glued.

Species

Sydney Blue, Eucalyptus saligna

Construction

Engineered

Core

Plantation Eucalypt ply

Wear Layer

0.6mm

Thickness

1/2" (13.5mm)

Width

5 3/8" (136mm)

7 3/8" (186mm)

Length

6 ft

Packaging

6 rows per box – 4 full length boards and two rows may be made up of multiple (up to 3) boards.

Square foot per box

5 3/8" - 16.07 sq ft

7 3/8" – 21.98 sq ft

Square foot per pallet

5 3/8" - 77 boxes -1237 sq ft

7 3/8" – 55 boxes- 1209 sq ft

Finish

13 Coat UV Urethane with Aluminum oxide

Sheen

Satin, 15-20%

Grade

Exclusive

Texture

Smooth

Profile

Valinge 2G glueless locking system, eased edge

Installation

Glue or Float, above, on or below grade. Please see our complete installation instructions available on our website.

Radiant Heat

Approved per installation instructions

Maintenance

Damp mop with Bona cleaner, refinish using Bona Recoat system and Traffic satin. For complete instructions please see our maintenance information on our website.

Warranty

25 year structural warranty | 15 year surface wear warranty

Please see our full warranty available on our website.

Outback Flooring USA

Six Campbell Ct, Novato, CA 94947 | 844 312 0002
sales@outbackflooringusa.com | www.outbackflooringusa.com

